

Sub  
A1

- 098206-07

wherein for said hot-pool a watchdog is monitoring said hot-pool's availability status, and  
 wherein said method is being executed by said watchdog, and  
 wherein said availability-signal is being repeated as long as at least one of said application-servers of said hot-pool is available, and  
 wherein within said first and said second step also a hot-pool-identification is inserted into said availability-database and is associated with said first- and said second-data-element.

[c6]

6. A computerized method for indicating availability according to claim 2, whereby as a second difference the difference of said recent availability-time and a previous availability-time is included in said measure of availability.

[c7]

7. A computerized method for indicating availability according to claim 5, whereby as a second difference the difference of said recent availability-time and a previous availability-time is included in said measure of availability.

[c8]

8. A computerized method for determining availability of one or multitude of application-servers for accepting application-service-request, said method comprising a first step of querying an availability-database for a first-data-element comprising a notification-period, said notification-period defining an upper time limit for a repetition-period of an availability-signal being repeated as long as said application-server is available, and for a second-data-element comprising for a recent availability-signal its time-stamp as recent availability-time, and  
 said method comprising a second step of determining a measure of availability of said application-server by comparing the difference of the current-time and said recent availability-time to said notification-period,  
 said method comprising a third step of issuing an application-service-request to said application-server only, if said measure of availability indicates availability of said indication-server.

[c9]

9. A computerized method for determining availability according to claim 8, wherein said measure of availability of the second step indicates unavailability of said application-server, if said difference exceeds said notification-period.

09682046-071301

SUB  
AI

[c10] 10. A computerized method for determining availability according to claim 8, wherein said method is querying in said first step also for a third-data-element comprising a previous availability-time for a previous availability-signal, and wherein in said second step also as a second difference the difference of said recent availability-time and said previous availability-time is included in said measure of availability.

[c11] 11. A computerized method for determining availability according to claim 8, wherein said measure of availability indicates unavailability of said application-server, if said difference exceeds said notification-period by a factor of N.

Sub A1  
[c12] 12. A computerized method for determining availability according to claim 10, wherein said method is being executed for a multitude of application-servers, and wherein in said third step a subset of application-servers, comprising application-servers for which said measure of availability indicates availability, is determined, and for each application-server within said subset its corresponding measure of availability is interpreted as a workload indication, and said application-service-request is being issued to an application-server with the lowest workload.

[c13] 13. A system indicating availability of one or a multitude of application-servers, said system comprising:  
a first device for inserting into an availability-database a first-data-element comprising a notification-period, said notification-period defining an upper time limit for a repetition period of an availability-signal being repeated as long as said application-server is available, and;  
said device further inserts into said availability-database a second-data-element comprising for each availability-signal its corresponding time stamp as availability-time, and;  
whereby, the difference of the current-time and a recent availability-time compared to said notification-period is representing a measure of availability of said application-server.

09582046-01301

[c14] 14. A data processing program for execution in a data processing system comprising software code portions, said software code portions comprises: a first software code portion for inserting into an availability-database a first-data-element comprising a notification-period, said notification-period defining an upper time limit for a repetition period of an availability-signal being repeated as long as said application-server is available, and; a second software code portion for inserting into said availability-database a second-data-element comprising for each availability-signal its corresponding time stamp as availability-time, and; whereby, the difference of the current-time and a recent availability-time compared to said notification-period is representing a measure of availability of said application-server.

[c15] 15. A computer program product stored on a computer usable medium, comprising a computer readable program embodied in said medium, including: readable code for inserting into an availability-database a first-data-element comprising a notification-period, said notification-period defining an upper time limit for a repetition period of an availability-signal being repeated as long as said application-server is available, and; readable code for inserting into said availability-database a second-data-element comprising for each availability-signal its corresponding time stamp as availability-time, and whereby, the difference of the current-time and a recent availability-time compared to said notification-period is representing a measure of availability of said application-server.

[c16] 16. A system for determining availability of one or multitude of application-servers for accepting application-service-request, said system comprising: a first device for querying an availability-database; for a first-data-element comprising a notification-period, said notification-period defining an upper time limit for a repetition-period of an availability-signal being repeated as long as said application-server is available; for a second-data-element comprising for a recent availability-signal its time-stamp as recent availability-time;

Sub  
A1

09582046-074301

said device determines a measure of availability of said application-server by comparing the difference of the current-time and said recent availability-time to said notification-period, and;  
 wherein said device issues an application-service-request to said application-server only, if said measure of availability indicates availability of said indication-server.

[c17]

17. A data processing program for execution in a data processing system comprising software code portions, said software code portions comprises:  
 a first software code portion for querying an availability-database;  
 for a first-data-element comprising a notification-period, said notification-period defining an upper time limit for a repetition-period of an availability-signal being repeated as long as said application-server is available;  
 for a second-data-element comprising for a recent availability-signal its time-stamp as recent availability-time;  
 a second software code portion to determine a measure of availability of said application-server by comparing the difference of the current-time and said recent availability-time to said notification-period, and;  
 a third software code portion to issue an application-service-request to said application-server only, if said measure of availability indicates availability of said indication-server.

[c18]

18. A computer program product stored on a computer usable medium, comprising a computer readable program embodied in said medium including:  
 readable code for querying an availability-database;  
 for a first-data-element comprising a notification-period, said notification-period defining an upper time limit for a repetition-period of an availability-signal being repeated as long as said application-server is available;  
 for a second-data-element comprising for a recent availability-signal its time-stamp as recent availability-time;  
 readable code for determining a measure of availability of said application-server by comparing the difference of the current-time and said recent availability-time to said notification-period; and  
 readable code for issuing an application-service-request to said application-

09682046-074304  
 T05T20-9408960

Sub  
 H1

Sub  
AI

server only if said measure of availability indicates availability of said  
indication-server.

09682046-071301